180 AFT-W 1.5

Cordless impact wrench 180 AFT-W 1.5 Wrench

+ Powerful cordless impact wrench in compact design and low weight
+ Lithium Ion battery technology
+ Blow-back proof due to impact mechanism

Order number: 12390301

Technical Data

Battery voltage	18	V
Battery capacity (Lithium Ion)	3,0	Ah
No-load speed	0...2.400	1/min.
No-load rate of percussion	0...3.200	1/min.
Width across corners	28	mm
Tool holder	½“ external square	
Max. torque	155	Nm
Max. torque (hard)	230	Nm
Metric bolts	M6 – M12	
Screw anchors up to	7,5	mm
Wood screws up to	12 x 100	mm
Plug screws up to	12	mm
Tool weight	1,4	kg
Dimensions (L x H)	172 x 56 x 209	mm

Product features

+ Robust aluminium die-cast gear housing
+ Reversible function
+ Highly luminous LED provides an optimal illumination of the working area
+ Battery pack with integrated LED can also be used as a lamp
+ Electronic switch provides stageless speed control
+ Quick stop for flush screwing
+ LED battery capacity display
+ Soft hand grip and rubberised electronic switch provide safe hold and fatigue-free working

Set includes

Second battery pack, CSL 30 LI fast charger with cable depot, professional carrying case

Noise/Vibration Information

vibration emission level a_h	10.3	m/s^2

uncertainty velue K	1.5	m/s^2
sound pressure level L_{pA}	95	dB(A)
uncertainty velue K	3.0	dB(A)
noise power level L_{wA}	106	dB(A)
uncertainty velue K	3.0	dB(A)

L_{pA} = A-rated sound pressure level, L_{wA} = A-rated sound power level
K = Measurement uncertainty value, a_h = Triaxial vibration emission level
Measurement values determined according to EN 60745.

Further noise and vibration information

KRESS-elektrik GmbH & Co. KG | P.O.Box 166, 72403 Bisingen, Germany
Phone +49 (0) 7476 / 87-300 | Fax +49 (0) 7476 / 87-191 | E-mail: **info@kress-elektrik.de** | **www.kress-elektrik.com**